



**RAINBOW TECHNOLOGY**  
Specialists in Utility Chemicals & Safety Items

261 Cahaba Valley Parkway - Pelham, AL 35124-1146

Tel: 1.800.637.6047 / 205.733.0333

Fax: 1.800.521.6896 / 205.733.8930

[www.rainbowtech.net](http://www.rainbowtech.net)

Woman-Owned Business Enterprise - Founded 1971

# Safety Data Sheet (SDS)

## 1 Identification of the substance and manufacturer

MANUFACTURER/DISTRIBUTOR: Rainbow Technology Corporation (800) 637-6047  
 CONTACT PERSON: Larry Joe Steele, Jr.  
**EMERGENCY PHONE (24 HRS): Chem-Tel Inc. (800) 255-3924**  
 TRADE NAME: Orange Chalk Temporary Water-Based Marking Paint  
 PRODUCT NUMBER: 46987  
 ISSUE DATE: June 8, 2015  
 REPLACES MSDS DATED: September 7, 2010

## 2 Hazard(s) identification

### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Carc. 2 H351 Suspected of causing cancer.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 STOT SE 3 H336 May cause drowsiness or dizziness.

### GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

### Signal word

### Hazard statements

Danger  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.  
 Suspected of causing cancer.  
 May cause drowsiness or dizziness.

### Precautionary statements

If medical advice is needed, have product container or label at hand.  
 Keep out of reach of children.  
 Read label before use.  
 Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Wash hands thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Do not handle until all safety precautions have been read and understood.  
 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a poison center/doctor if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

### Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

67-64-1	Acetone	26.06%
1317-65-3	Calcium Carbonate	19.36%
74-98-6	propane	17.64%
67-63-0	isopropyl alcohol	15.18%
106-97-8	n-butane	10.36%
2807-30-9	Glycol Ether EP	3.72%

# Safety Data Sheet (SDS)

## 4 First-aid measures

<b>After inhalation:</b>	Supply fresh air; consult doctor in case of complaints.
<b>After skin contact:</b>	Remove contaminated clothing. Wash exposed area with soap and water.
<b>After eye contact:</b>	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
<b>After swallowing:</b>	Rinse mouth with water. Do not induce vomiting.
<b>Most important symptoms and effects:</b>	Dizziness
<b>Indication of any immediate medical</b>	
<b>Protective equipment for firefighters:</b>	A respiratory protective device may be necessary.

## 6 Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures:</b>	Use respiratory protective device against the effects of fumes/dust/aerosol.
<b>Methods and material for containment and cleaning up:</b>	Absorb liquid components with liquid-binding material.

## 7 Handling and storage

<b>Precautions for safe handling</b>	Use only in well ventilated areas.
<b>Storage requirements:</b>	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

## 8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:	
<b>67-64-1 Acetone</b>	
PEL (USA)	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m <sup>3</sup> , (500) NIC-250 ppm BEI
<b>74-98-6 propane</b>	
PEL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV (USA)	refer to Appendix F
<b>67-63-0 isopropyl alcohol</b>	
PEL (USA)	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL (USA)	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV (USA)	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm Long-term value: 492 mg/m <sup>3</sup> , 200 ppm BEI
<b>106-97-8 n-butane</b>	
REL (USA)	Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm
Ingredients with biological limit values:	
<b>67-64-1 Acetone</b>	
BEI (USA)	40 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
<b>67-63-0 isopropyl alcohol</b>	
BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

<b>Hygienic protection:</b>	Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.
<b>Breathing equipment:</b>	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
<b>Hand protection:</b>	Protective gloves. The glove material must be impermeable and resistant to the substance.
<b>Eye protection:</b>	Tightly sealed goggles

# Safety Data Sheet (SDS)

## 9 Physical and chemical properties

<b>Appearance:</b>	Aerosol.
<b>Odor:</b>	Aromatic
<b>Odor threshold:</b>	Not determined.
<b>pH-value:</b>	Not determined.
<b>Melting point/Melting range</b>	Undetermined.
<b>Boiling point:</b>	-44 °C (-47 °F)
<b>Flash point:</b>	-19 °C (-2 °F)
<b>Flammability (solid, gas):</b>	Extremely flammable.
<b>Decomposition temperature:</b>	Not determined.
<b>Auto igniting:</b>	Product is not self-igniting.
<b>Danger of explosion:</b>	In use, may form flammable/explosive vapour-air mixture.
<b>Lower Explosion Limit:</b>	1.5 Vol %
<b>Upper Explosion Limit:</b>	12.0 Vol %
<b>Vapor pressure:</b>	Not determined.
<b>Relative Density:</b>	Between 0.77 and 0.85 (Water equals 1.00)
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not applicable.
<b>Partition coefficient: n-octanol/water:</b>	Not determined.
<b>Solubility:</b>	Not determined.
<b>Viscosity:</b>	Not determined.
<b>VOC content:</b>	542.5 g/l / 4.53 lb/gl
<b>VOC content (less exempt solvents):</b>	48.0 %
<b>Water:</b>	1.6 %
<b>MIR Value:</b>	0.69
<b>Solids content:</b>	23.6 %

## 10 Stability and reactivity

<b>Reactivity:</b>	Stable at normal temperatures.
<b>Conditions to avoid:</b>	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
<b>Chemical stability:</b>	Not fully evaluated.
<b>Possibility of hazardous reactions:</b>	No dangerous reactions known.
<b>Incompatible materials:</b>	No further relevant information available.
<b>Hazardous decomposition:</b>	No dangerous decomposition products known.

## 11 Toxicological information

### LD/LC50 values that are relevant for classification:

#### 67-63-0 isopropyl alcohol

Oral	LD50	4570 mg/kg (rat)
Dermal	LD50	13400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

#### 106-97-8 n-butane

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

<b>Information on toxicological effects:</b>	No data available.
<b>Skin effects:</b>	No irritant effect.
<b>Eye effects:</b>	Irritating effect.
<b>Sensitization:</b>	No sensitizing effects known.

### Carcinogenic categories

#### IARC (International Agency for Research on Cancer)

67-63-0	isopropyl alcohol	3
---------	-------------------	---

#### NTP (National Toxicology Program)

None of the ingredients is listed.

## 12 Ecological information

<b>Aquatic toxicity:</b>	Hazardous for water, do not empty into drains.
<b>Persistence and degradability:</b>	The product is degradable after prolonged exposure to natural weathering processes.
<b>Bioaccumulative potential:</b>	No further relevant information available.
<b>Mobility in soil:</b>	No further relevant information available.
<b>Other adverse effects:</b>	No further relevant information available.

# Safety Data Sheet (SDS)

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

**UN-Number** UN1950  
**DOT** N/A  
**DOT** Consumer Commodity ORM-D  
Aerosols, flammable  
1950 Aerosols  
**ADR**  
**Transport hazard class(es):**  
**Class** 2.1  
**Marine pollutant:** No  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U  
**Quantity limitations** On passenger aircraft/rail: 75 kg  
On cargo aircraft only: 150 kg

**ADR**  
**Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity

### IMDG

**Limited quantities (LQ)** 1L  
**Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity  
**Packaging Group:** --  
**UN "Model Regulation":** UN1950, Aerosols, 2.1

## 15 Regulatory information

### SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

### SARA Section 313 (Specific toxic chemical listings):

67-63-0 isopropyl alcohol

**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

### California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

### CANADIAN ENVIRONMENTAL

**PROTECTION ACT:** All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

### EPA:

67-64-1 Acetone

## 16 Other information

**Contact:** Larry Joe Steeley, Jr. 800-637-6047  
**Date of preparation / last revision** 06/08/2015 / -