

Distributed by
Rainbow Technology Corp.
Tel: 1.800.637.6047 / 205.733.0333
RTC Product #77200, 77220

Distributed by: **Rainbow Technology Corp.**
1.800.637.6047 or 205.733.0333
RTC Product # 77200 & 77220



U.S. MATERIAL SAFETY DATA SHEET

D'Gel Cable Gel Solvent

Section 1 • Product and Company Identification

Manufacturer's Name: PT Technologies

Chemical Family: Hydrocarbons

Trade Name: PT D'Gel

Telephone Number: 770-243-8810

Address:
4647 Hugh Howell Road
Tucker, GA USA 30085-5052

Emergency Telephone Numbers:

1-800-424-9300 Chemtrec;
Outside U.S.: (703) 527-3887

Packaging / part numbers:

Individual wipe towels,	61244	One 3 quart sealed poly bag in a pail	61296
12 field splice kit	61202	1 gal. (3.78 liters)	61201
32 fl.oz. bottle (.946 liters)	61232	55 gal. poly drum (208 liters)	61255

PLAIN LANGUAGE HAZARD SUMMARY

Material Safety Data Sheets can be confusing. Federal and State laws require us to include a great deal of technical information that probably won't help the non-professional. LPS includes this "PLAIN LANGUAGE HAZARD SUMMARY" to address the questions and concerns of the average worker. If you have additional health, safety or product questions, don't hesitate to call us at 800/241-8334.

Worker Toxicity

PT D'GEL CABLE GEL SOLVENT is designed to remove grime, "icky-pic," and other contaminants from electrical and telecommunications cables during splicing operations. It contains d-limonene and paraffinic hydrocarbons that can be irritating to skin. We suggest you wear gloves and avoid extended exposure to unprotected skin. Don't get it in your eyes (it stings), or breathe large amounts of the vapor, (it will dry out your nasal passages and if you breathe large amounts in poorly ventilated areas it can make you dizzy and even sick). Don't atomize PT D'GEL CABLE GEL SOLVENT for extended periods without adequate ventilation. If you're going to perform work involving a lot of product in a poorly ventilated area, use of a respirator or even a self-contained breathing apparatus may be necessary. For more exposure and first aid information, refer to MSDS Sections 2, 8 and 11.

Flammability

PT D'GEL CABLE GEL SOLVENT generates a "flame extension" when atomized into an ignition source (flame, arc, etc.), but in having a flash point above 141°F, it is generally safe to use for most industrial applications. Store product away from heat sources and do not spray into live electrical equipment.

Disposal

If you spill PT D'GEL CABLE GEL SOLVENT, notify the proper environmental or safety department at your company right away. If PT D'GEL CABLE GEL SOLVENT becomes contaminated with another substance and is rendered unusable for cleaning, the resulting mixture may fall under at least one hazardous classification.

Safety Data Sheet (SDS)



U.S. MATERIAL SAFETY DATA SHEET D'Gel Cable Gel Solvent

Section 2 • Hazards Identification

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Emergency Overview: CAUTION: Combustible liquid and vapor. May cause skin irritation. May cause sensitization by skin contact. May cause lung damage if swallowed.

Primary route(s) of entry: Skin and Eye contact. Inhalation.

Potential Acute Health Effects:

Eyes Irritating to eyes

Skin Repeated exposure may cause skin dryness or cracking.

Inhalation: Excessive inhalation of vapors can cause irritation of the respiratory tract, nausea, dizziness or headache.

Ingestion: Product has a low order of acute oral toxicity, but ingestion of large quantities may cause nausea, vomiting, and gastrointestinal irritation. May cause injury if aspirated into lungs.

Potential Chronic Health Effects:

Carcinogenic Effects: NTP: No IARC: No OSHA: No

Mutagenic Effects: None

Teratogenic Effects: None

Medical conditions aggravated by exposure: Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

Signs and Symptoms

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects. Swallowing may cause vomiting which in turn can lead to aspiration into lungs.

Section 3 • Composition / Information on Ingredients

Component	CASRN	Percent by Weight
Paraffinic hydrocarbon	64771-72-8	70 - 90%
d-limonene	5989-27-5	10 - 20%

Section 4 • First Aid Measures

Eyes: Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. Do not use eye ointment. Seek medical attention immediately.

Skin: Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. Do not use ointments. Seek medical attention if irritation persists.

Safety Data Sheet (SDS)



U.S. MATERIAL SAFETY DATA SHEET D'Gel Cable Gel Solvent

Section 2 • Hazards Identification

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Emergency Overview: CAUTION: Combustible liquid and vapor. May cause skin irritation. May cause sensitization by skin contact. May cause lung damage if swallowed.

Primary route(s) of entry: Skin and Eye contact. Inhalation.

Potential Acute Health Effects:

Eyes Irritating to eyes

Skin Repeated exposure may cause skin dryness or cracking.

Inhalation: Excessive inhalation of vapors can cause irritation of the respiratory tract, nausea, dizziness or headache.

Ingestion: Product has a low order of acute oral toxicity, but ingestion of large quantities may cause nausea, vomiting, and gastrointestinal irritation. May cause injury if aspirated into lungs.

Potential Chronic Health Effects:

Carcinogenic Effects: NTP: No IARC: No OSHA: No

Mutagenic Effects: None

Teratogenic Effects: None

Medical conditions aggravated by exposure: Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

Signs and Symptoms

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects. Swallowing may cause vomiting which in turn can lead to aspiration into lungs.

Section 3 • Composition / Information on Ingredients

Component	CASRN	Percent by Weight
Paraffinic hydrocarbon	64771-72-8	70 - 90%
d-limonene	5989-27-5	10 - 20%

Section 4 • First Aid Measures

Eyes: Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. Do not use eye ointment. Seek medical attention immediately.

Skin: Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. Do not use ointments. Seek medical attention if irritation persists.

Safety Data Sheet (SDS)



U.S. MATERIAL SAFETY DATA SHEET

D'Gel Cable Gel Solvent

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Personal Protection:

Eyes: Safety glasses.

Respiratory : Use organic vapor cartridge type respirator if ventilation is inadequate.

Hands: Use nitrile gloves.

General Hygiene Considerations: Wash thoroughly after handling. Have eye-wash facilities immediately available.

Section 9 • Physical and Chemical Properties

Appearance:	Liquid.	Color:	Colorless / water-white
Odor/Taste:	Orange.	pH:	Not Applicable
Solubility Description:	Miscible at all proportions	Evaporation Rate:	<10 (BuAc=100)
Boiling Point (°C):	193°C (379°F) @ 760mmHg	Flash Point (°C):	72°C (161°F)
Specific Gravity (Water=1):	0.78-0.80 @ 20 °C	Flash Point Method:	Tag-Closed Cup.
Vapour Density (air=1):	>1	Auto Ignition Temperature (°C):	Not Established
Flammable limits (estimated):	LOWER: 1.3% UPPER: 8.9%	Partition Coefficient (octanol/water):	<1
Viscosity:	<3 cSt @ 25°C	Volatiles:	97%

Section 10 • Stability and Reactivity

Stability and Reactivity: The product is stable.

Incompatibility with Various Substances: Extremely reactive or incompatible with oxidizing agents.

Hazardous decomposition products: These products are carbon oxides (CO, CO₂)

Hazardous polymerization: Will not occur.

Section 11 • Toxicological Information

Acute and Chronic Toxicity

A: General Product Information

Following exposure to vapors, this material can produce central nervous system depression. High atmospheric concentrations can result in eye, nasal and respiratory tract irritation. However, if handled in accordance with good industrial hygiene practice, this product will not present a significant hazard in the workplace.

Safety Data Sheet (SDS)



U.S. MATERIAL SAFETY DATA SHEET

D'Gel Cable Gel Solvent

Ingredients	CASRN	LC-50	LD-50
Paraffinic hydrocarbon	64771-72-8	Not established	> 5000 mg/kg (oral, rat)
d-limonene	5989-27-5	Not established	>5000 mg/kg (oral, rabbit) >5000 mg/kg (dermal, rabbit)

Section 12 • Ecological Information

Mobility:	Semi-volatile. Readily absorbed into soil.	Persistence and degradability:	Only slightly biodegradable.
Bioaccumulative potential:	No bioaccumulation potential	Other adverse effects:	None known.

Component Data: Acute Aquatic Toxicity

Component	CASRN	Test	Species	Results
Paraffinic hydrocarbon	64771-72-8	Not Available		
d-limonene	5989-27-5	4-day LC ₅₀	Oncorhynchus mykiss	35,000 µg/L
		96-hour EC ₅₀	Pimephales promelas	1,490,000 µg/L

Section 13 • Disposal Considerations

Waste Status:	In its purchased form, this product is not classified as hazardous waste.
Disposal:	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Note:	Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive than federal laws and regulations.

Section 14 • Transport Information

This product is not regulated by any mode of transportation.

Section 15 • Regulatory information

U.S. Federal Regulations:	<p>TSCA 8(b) inventory: All of the ingredients are listed on the TSCA inventory or are exempt.</p> <p>RCRA Hazardous Waste No.: none.</p> <p>CERCLA Sections 102a/103 Hazardous Substances (40 CFR part 370) Reportable Quantity: none</p> <p>SARA TITLE III Sections 311/312 hazardous Categorization (40 CFR part 370): Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard.</p> <p>SARA TITLE III Section 313: No</p>
----------------------------------	---

Safety Data Sheet (SDS)



U.S. MATERIAL SAFETY DATA SHEET D'Gel Cable Gel Solvent

Hazardous Air Pollutants (U.S. EPA): None

State Regulations: **New Jersey RTK:** Paraffinic hydrocarbon (CASRN: 64771-72-8), d-limonene (CASRN: 5989-27-5), Sodium dioctyl sulfosuccinate (CASRN: 577-11-7), Glycols, polyethylene-polypropylene (9003-11-6)

California Proposition 65: None.

California and OTC States: This product is not regulated as a consumer item.

Section 16 • Other Information

<p>MSDS#461201 Responsible Name: Ed Williams Technical Manager</p>	<p style="text-align: center;">HMIS</p> <p>Health: 1 Flammability: 2 Reactivity: 0</p>	<p style="text-align: center;">NFPA</p> <p style="text-align: center;">flammability</p> <div style="text-align: center;"> </div> <p style="text-align: center;">health reactivity</p>
---	---	---

Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Ed Williams, Technical Manager
LPS Laboratories
A division of Illinois Tool Works

Form #461201