

Safety Data Sheet (SDS)

Section 1 – Product and Company Information

Product Name:	C-Desiccant, 4 oz bag (DesiCom C)
Product Use:	Desiccant, absorbent
Grades:	Silica gel non-indicating
Synonyms:	Amorphous silica gel, SiO ₂ , silicon dioxide (amorphous)
Product Number:	79358
Manufacturer/Distributor:	Rainbow Technology Corporation (800) 637-6047
Contact Person:	Larry Joe Steeley, Jr.
Emergency Phone # (24 HRS)	Chem-Tel 800-255-3924
Issue Date:	May 27, 2014
Replaces MSDS Dated:	October 6, 2009

Section 2 – Composition / Information on Ingredients

Component Name	CAS Number	% by Weight
Synthetic amorphous silica gel (SiO ₂)	112926-00-8	90 – 99
Kraft Paper	Unlisted	1 - 10

While this material is not classified as hazardous under OSHA regulations, this MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.

Section 3 – Hazard Identification

Emergency Overview: A packet containing a clear granular material that poses little or no immediate hazard. The packet is made of brown kraft paper on both sides. The silica gel is not combustible, but the kraft paper packaging is combustible.

Potential Health Effects:

Eyes: None

Skin: None

Ingestion: Ingestion is very unlikely.

Inhalation: None

Medical Effects Generally Aggravated by Exposure: None

Chronic Effects/Carcinogenicity: None

Section 4 – First Aid Measures

Eyes: Rinse the eyes well with water while lifting eye lids. If irritation persists, consult a physician

Skin: Wash affected area with soap and water.

Ingestion: Ingestion is very unlikely.

Inhalation: Remove the affected person to fresh air and get medical attention if necessary.

Notes to Physician: Not applicable

Safety Data Sheet (SDS)

Product No. 79358 C-Desiccant, 4 oz bag (DesiCom C)

Section 5 – Fire Fighting Measures

Flammable Properties: Not flammable**Flash Point:** Not applicable**Method:** Not applicable**Flammable Limits:** Not flammable**Lower Flammability Limit:** Not applicable**Upper Flammability Limit:** Not applicable**Autoignition Temperature:** Not applicable**Hazardous Combustion Products:** Not applicable**Extinguishing Media:** Use extinguishing media that is appropriate for the surrounding fire. Silica gel is not combustible but the kraft paper packaging is combustible.**Fire Fighting Instructions:** The silica gel is not combustible but the kraft paper packaging is combustible.**Unusual Fire and Explosion Hazards:** None

Section 6 – Accidental Release Measures

Spill: Sweep or vacuum up and place the spilled material in a waste disposal container. Avoid raising dust. Wash with soap and water after handling.

Section 7 – Handling and Storage

Handling: Avoid raising dust and minimize the contact between worker and the material. Practice good hygienic work practices.**Storage:** Store in a cool, dry location. Keep in sealed containers away from moisture. The silica gel will readily adsorb moisture.

Section 8 – Exposure Controls/Personal Protection

Engineering Controls: Not required.**Respiratory Protection:** Not required.**Skin Protection:** Light gloves will protect against abrasion and drying of the skin.**Eye Protection:** Not required.

Component Name	Exposure Limits		
	OSHA PEL	ACGIH TLV	Other Recommended Limits
Silica gel	TWA 20 mppcf (80 mg / m ³ % SiO ₂)	TWA 10 mg / m ³	NIOSH REL TWA 6 mg / m ³ IDLH 3000 mg / m ³

Safety Data Sheet (SDS)

Product No. 79358 C-Desiccant, 4 oz bag (DesiCom C)

Section 9 – Physical and Chemical Properties

Appearance:	Brown packets	Vapor Density:	Not applicable
Odor:	None	Boiling Point:	4046° F (2230° C) (Silica Gel)
Physical State:	Packets	Melting Point:	3110° F (1710° C) (Silica Gel)
PH:	Not applicable	Solubility:	Insoluble in water
Vapor Pressure:	Not applicable	Specific Gravity:	2.1

Section 10 – Stability and Reactivity

Stability: Stable**Conditions to avoid:** Moisture and high humidity environments.**Incompatibility:** Water, fluorine, oxygen difluoride, chlorine trifluoride**Hazardous Decomposition Products:** None**Hazardous Polymerization:** Will not occur

Section 11 – Toxicological Information

This product and its components are not listed on the IARC, NTP or OSHA Carcinogen lists.

Animal Toxicology Tests for DOT Hazard classification
(Tests Conducted on finely ground silica gel)

1 - hour LC₅₀ (rat) > 2 mg / l
 48 - hour oral LD₅₀ (rat) est. > 31,600 mg / kg
 48 - hour dermal LD₅₀ (rabbit) est. > 2,000 mg / kg
 Considered an ocular irritant

Human Toxicology Silica gel is a synthetic amorphous silica not to be confused with crystalline silica. Epidemiological studies indicate low potential for adverse health effects. In the activated form, silica gel acts as a desiccant and can cause a drying irritation of the mucous membranes and skin in cases of severe exposure. Rainbow Technology Corporation does not know of any medical conditions that are abnormally aggravated by exposure to silica gel. The primary route of entry is inhalation of dust.

Section 12 – Ecological Information

Not known to have any adverse effect on the aquatic environment. Silica gel is insoluble and non-toxic.

Section 13 – Disposal Information

Disposal Information If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Materials of a hazardous nature that contact the product

Safety Data Sheet (SDS)

Page 4 of 4

Product No. 79358 C-Desiccant, 4 oz bag (DesiCom C)

during normal use may be retained on the product. The user of the product must identify the hazards associated with the retained material in order to assess the waste disposal options. Dispose according to federal, state and local regulations.

Section 14 – Transportation Information

U.S. Department of Transportation Shipping Name: Not classified as a hazardous material. Not regulated.

Section 15 – Regulatory Information (Not meant to be all inclusive - selected regulations represented)

TSCA Listed: Yes (Ingredients)

DSL/NDSL (Canadian) Listed: Yes (Ingredients)

OSHA: TWA 20 mppcf (80 mg / m³ % SiO₂)

NIOSH: REL TWA 6 mg / m³ IDLH 3,000 mg / m³
Animal tests conducted in 1976 - 1978. 18 month exposure at 15 mg / m³ showed silica deposition in respiratory macrophages and lymph nodes, minimum lung impairment, no silicosis

EPA: This product contains no toxic chemicals in excess of the applicable de minimis concentration as specified under 313 of Title III SARA.

DOT: Not classified as a hazardous material.

Section 16 – Other Information

HMIS – Hazardous Materials Identification System

HMIS Rating	
Health	0
Flammability	0
Reactivity	0

0 - minimal hazard, 1 - slight hazard, 2 - moderate hazard, 3 - serious hazard, 4 - severe hazard

The information provided herein was believed to be accurate at the time of preparation and prepared from a compilation of sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of this product, and to determine the suitability of the product for its intended use.