

**Safety Data Sheet**  
acc. to OSHA HCS

Printing Date 08/25/2015

Revision Number 1

Revision Date 08/25/2015

**1 Identification**

- **Product identifier**
- **Trade name: Q-Set 250 Part B**
- **Relevant identified uses of the substance or mixture.** Pole Setting Foam
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Royal Adhesives & Sealants Canada Ltd  
266 Humberline Drive - Toronto, Ontario, Canada M9W 5X1  
Tel. +1 416-679-5676 Fax: +1 416-679-0511
- **Information department:** Environment protection department.
- **Emergency telephone number:**  
Emergency Telephone Number: CANUTEC Collect: (613) 996-6666 (24-hour hotline)

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Danger

- **Hazard statements**

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 2)

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 08/25/2015

Revision Number 1

Revision Date 08/25/2015

**Trade name: Q-Set 250 Part B**

(Contd. of page 1)

*May cause an allergic skin reaction.*

*Suspected of causing cancer.*

*May cause respiratory irritation.*

*May cause damage to organs through prolonged or repeated exposure.*

**· Precautionary statements**

*Do not breathe dust/fume/gas/mist/vapors/spray.*

*Wear respiratory protection.*

*Wear protective gloves.*

*Wear eye protection / face protection.*

*Wash thoroughly after handling.*

*Use only outdoors or in a well-ventilated area.*

*Contaminated work clothing must not be allowed out of the workplace.*

*Obtain special instructions before use.*

*Do not handle until all safety precautions have been read and understood.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*Specific treatment (see on this label).*

*If experiencing respiratory symptoms: Call a poison center/doctor.*

*IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.*

*Call a poison center/doctor if you feel unwell.*

*Wash contaminated clothing before reuse.*

*IF exposed or concerned: Get medical advice/attention.*

*If skin irritation or rash occurs: Get medical advice/attention.*

*If eye irritation persists: Get medical advice/attention.*

*Get medical advice/attention if you feel unwell.*

*If on skin: Wash with plenty of water.*

*Take off contaminated clothing and wash it before reuse.*

*Store locked up.*

*Store in a well-ventilated place. Keep container tightly closed.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

**· Classification system:**

**· NFPA ratings (scale 0 - 4)**




Health = 2

Fire = 1

Reactivity = 1

**· HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 1

Physical Hazard = 1

**· Other hazards**

**· Results of PBT and vPvB assessment**

**· PBT:** Not applicable.

**· vPvB:** Not applicable.

### \* 3 Composition/information on ingredients

**· Chemical characterization: Mixtures**

**· Description: Polyurethane**

(Contd. on page 3)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 08/25/2015

Revision Number 1

Revision Date 08/25/2015

Trade name: Q-Set 250 Part B

(Contd. of page 2)

**Hazardous components:**

101-68-8	4,4'-methylenediphenyl diisocyanate	25-50%
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	25-50%

### 4 First-aid measures

**Description of first aid measures**
**After inhalation:**

Remove to fresh air. If not breathing, administer artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

**After skin contact:**

Wipe excess from skin.

Immediately wash with water and soap and rinse thoroughly.

**After eye contact:**

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.

**After swallowing:** Do not induce vomiting; immediately call for medical help.

**Information for doctor:**

**Most important symptoms and effects, both acute and delayed** No further relevant information available.

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

**Extinguishing media**
**Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.

Use fire fighting measures that suit the environment.

**Special hazards arising from the substance or mixture**

Closed containers may forcibly rupture under extreme heat or when contents are contaminated with water.

Carbon Dioxide (CO<sub>2</sub>) is formed.

**Advice for firefighters**
**Protective equipment:** Protective clothing and respiratory protective device.

### 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

**Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Cover spilled material with neutralization solution (see below) and mix. Wait 15 minutes. Collect material in open-head metal containers. Repeat neutralization and cleaning process until surface is decontaminated. Apply drum lid but DO NOT secure. Allow containers to vent for 72 hours to let carbon dioxide escape.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

Ensure adequate ventilation.

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 08/25/2015

Revision Number 1

Revision Date 08/25/2015

**Trade name: Q-Set 250 Part B**

(Contd. of page 3)

See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Product reacts with water. Reaction may produce heat and/or gases. Container may rupture from gas generation in a fire situation. This reaction may be violent.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Keep containers tightly closed when not in use. Protect from atmospheric moisture.
- **Information about storage in one common storage facility:** Store away from water.
- **Further information about storage conditions:**  
Protect from humidity and water.  
Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

#### 101-68-8 4,4'-methylenediphenyl diisocyanate

PEL	Ceiling limit value: 0.2 mg/m <sup>3</sup> , 0.02 ppm
REL	Long-term value: 0.05 mg/m <sup>3</sup> , 0.005 ppm Ceiling limit value: 0.2* mg/m <sup>3</sup> , 0.02* ppm *10-min
TLV	Long-term value: 0.051 mg/m <sup>3</sup> , 0.005 ppm

- **Additional information:**  
MDI products have poor warning properties, since recognition of an odor is far above the TLV. Observe OSHA regulations for respirator use (29 CFR 1910.134).  
The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment (see listings below)**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
Airborne MDI concentrations greater than the ACGIH TLV-TWA or OSHA PEL can occur in inadequately ventilated environments when MDI is sprayed or heated. In such cases respiratory protection is require.  
Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing Date 08/25/2015

Revision Number 1

Revision Date 08/25/2015

Trade name: Q-Set 250 Part B

(Contd. of page 4)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

Butyl rubber, BR

Chloroprene rubber, CR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses with side shields.



Tightly sealed goggles

· **Body protection:**

Apron

Protective work clothing

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Dark Amber

· **Odor:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point: Undetermined.

Boiling point: 200 °C (392 °F)

· **Flash point:** 220 °C (428 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 400 °C (752 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Flammable limits:**

Lower: 0.4 Vol %

(Contd. on page 6)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 08/25/2015

Revision Number 1

Revision Date 08/25/2015

Trade name: **Q-Set 250 Part B**

(Contd. of page 5)

· <b>Vapor pressure:</b>	Not determined.
· <b>Specific gravity at 20 °C (68 °F):</b>	1.2 g/cm <sup>3</sup> (10.014 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.0 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
Contact with moisture, other materials that react with isocyanates, or temperatures above 350F (177C), may cause polymerization.
- **Possibility of hazardous reactions**  
Violent reaction with water at high temperatures.  
May produce violent reactions with bases and numerous organic substances including alcohols and amines.  
MDI reacts slowly with water to form Carbon Dioxide gas. This gas can cause sealed containers to expand and possibly rupture. Contact with moisture, other materials that react with isocyanates, or temperatures above 350F, may cause polymerization.
- **Conditions to avoid** Moisture
- **Incompatible materials:**  
Reacts with amines, caustic alkali solutions, alcohols, ammonia, oxidizers, acids, polyols.  
Reacts with water forming carbon dioxide-may rupture sealed containers if contaminated with water.  
May produce violent reactions with bases and numerous organic substances including alcohols and amines.  
copper and copper alloys.
- **Hazardous decomposition products:**  
Nitrogen oxides  
Carbon monoxide and carbon dioxide  
Isocyanate  
Isocyanic acid

### 11 Toxicological information

- **Information on toxicological effects**
  - **Acute toxicity:**
- |   |      |                    |
|---|------|--------------------|
| · <b>LD/LC50 values that are relevant for classification:</b> |      |                    |
| <b>101-68-8 4,4'-methylenediphenyl diisocyanate</b>           |      |                    |
| Oral  | LD50 | 2200 mg/kg (mouse) |

(Contd. on page 7)

# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 08/25/2015

Revision Number 1

Revision Date 08/25/2015

Trade name: **Q-Set 250 Part B**

(Contd. of page 6)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:**  
Causes serious eye irritation.  
Vapors may be irritating to the eyes.
- **Sensitization:**  
Inhalation - Sensitization possible through inhalation.  
Skin Contact - Sensitization possible through skin contact.
- **Additional toxicological information:**  
May cause allergic respiratory reaction.

Animal tests have indicated that respiratory sensitization can result from skin contact with MDI. Use skin protection.

Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product.

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

101-68-8	4,4'-methylenediphenyl diisocyanate	3
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### \* 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** At present there are no ecotoxicological assessments.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### \* 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Must be specially treated adhering to official regulations.

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing Date 08/25/2015

Revision Number 1

Revision Date 08/25/2015

Trade name: Q-Set 250 Part B

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

## \* 14 Transport information

- |  |  |
|--|--|
| · <b>UN-Number</b><br>· DOT, ADR, ADN, IMDG, IATA                                | not regulated  |
| · <b>UN proper shipping name</b><br>· DOT, ADR, ADN, IMDG, IATA                  | not regulated  |
| · <b>Transport hazard class(es)</b><br>· DOT, ADR, ADN, IMDG, IATA<br>· Class    | not regulated  |
| · <b>Packing group</b><br>· DOT, ADR, IMDG, IATA                                 | not regulated  |
| · <b>Environmental hazards:</b>  | Not applicable.  |
| · <b>Special precautions for user</b>  | Not applicable.  |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable.  |
| · <b>Transport/Additional information:</b>                                       | MDI (CAS 101-68-8) exhibits a CERCLA RQ equal to 5,000 pounds. Quantities less than the RQ amount are not regulated in transportation. |
| · <b>UN "Model Regulation":</b>  | -  |

## \* 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
  - **Sara**
- |  |
|--|
| · <b>Section 355 (extremely hazardous substances):</b>   |
| None of the ingredients is listed.   |
| · <b>Section 313 (Specific toxic chemical listings):</b>   |
| All ingredients are listed.  |
| · <b>TSCA (Toxic Substances Control Act):</b>  |
| All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.           |
| · <b>Proposition 65</b>  |
| · <b>Chemicals known to cause cancer:</b>  |
| None of the ingredients is listed.   |
| · <b>Chemicals known to cause reproductive toxicity:</b>   |
| None of the ingredients is listed.   |
| · <b>(DSL) Canada Domestic Substance List</b>  |
| All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements. |

(Contd. on page 9)

USA



# Safety Data Sheet

## acc. to OSHA HCS

Printing Date 08/25/2015

Revision Number 1

Revision Date 08/25/2015

**Trade name: Q-Set 250 Part B**

(Contd. of page 8)

**· Cancerogenity categories**
**· EPA (Environmental Protection Agency)**

101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	CBD

**· TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients listed.

**· MAK (German Maximum Workplace Concentration)**

101-68-8	4,4'-methylenediphenyl diisocyanate	4
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	4

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**· National regulations:**
**· Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

**· Department issuing SDS:** Environment protection department.

**· Creation Date:** 07/13/2015

**· Date of preparation / last revision** 08/25/2015 / -

**· Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2