

Distributed by:  
**Rainbow Technology Corp.**  
**1.800.637.6047 or 205.733.0333**  
**Product # 4669**

**AerVOE Rust Proof Paint - Aerosol**



# Material Safety Data Sheet

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know.

The following material safety data sheet covers the hazardous ingredients associated with more than one color aerosol product. As per 29 CFR 1900.1200 paragraph (g); whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following AerVOE aerosol products.

**PRODUCT NAME:** Rust Proof Paint (Solvent Based)

- |                   |                  |                         |
|-------------------|------------------|-------------------------|
| 300 Safety Purple | 308 Brite Red    | 321 Equipment Orange    |
| 301 Safety Red    | 312 Flat Black   | 333 Dark Gray (ANSI-33) |
| 302 Safety Yellow | 313 Flat White   | 342 Semi-Flat Black     |
| 303 Safety Blue   | 314 Brown        | 344 Satin Black         |
| 304 Safety Green  | 317 Tan          | 348 Meter Green         |
| 305 Safety Orange | 318 Light Blue   | 349 Meter Gray(ANSI-49) |
| 306 Safety Black  | 319 Royal Blue   | 361 Lt. Gray (ANSI-61)  |
| 307 Safety White  | 320 Forest Green | 395 Dove Gray           |

**SECTION I - MANUFACTURER IDENTIFICATION**

**MANUFACTURER'S NAME:** AerVOE Industries, Inc.  
**INFORMATION PHONE:** 775-782-0100  
**DATE REVISED:** November 9, 2006

**ADDRESS:** 1198 Mark Circle, Gardnerville, NV 89410  
**EMERGENCY PHONE:** 1-800-424-9300  
**REASON REVISED:** Updated

**SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION  
 OCCUPATIONAL EXPOSURE LIMITS**

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
Acetone (CAS 67-64-1)	15 - 40	1000 ppm	500 ppm	5800 mg / kg (Rat-Oral)	21000 ppm / 8 hr (Rat-Inha)
Hydrocarbon Propellant (CAS 68476-86-8)	10 - 30	1000 ppm	1000 ppm	N / AV	N / AV
Aliphatic Petroleum Distillates (CAS 64742-89-8)	10 - 30	N / AV	300 ppm	N / AV	N / AV
Dipropylene Glycol Methyl Ether (CAS 34590-94-8)	1 - 5	100 ppm (skin)	100 ppm (skin) 150 ppm	N / AV	N / AV
<b>307, 312, and 313 Also Contain:</b> Aliphatic Hydrocarbon (CAS 8052-41-3)	1 - 5	500 ppm	100 ppm	N / AV	N / AV

\*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

**NOTE:** N / AP = Not Applicable N / AV = Not Available

Distributed by:  
**Rainbow Technology Corp.**  
**1.800.637.6047 or 205.733.0333**  
**Product # 4669**

### SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

**BOILING POINT:** N / AP  
**VAPOR DENSITY:** Heavier than air  
**EVAPORATION RATE:** Faster than n-Butyl Acetate  
**SPECIFIC GRAVITY (H2O=1):** . 0.9  
**SOLUBILITY IN WATER:** Negligible  
**APPEARANCE AND ODOR:** Opaque liquid with a ketone odor.

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT:** < 0° F (-18° C)  
**EXTINGUISHING MEDIA:** Carbon dioxide, dry chemical, water spray.  
**SPECIAL FIRE FIGHTING PROCEDURES:** Use water spray to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.  
**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Treat as cylinders of compressed gas. Closed containers may rupture due to pressure build up from extreme temperature.  
**FLAMMABILITY:** Yes - Flammable aerosol under conditions of sparks, flame, or hot surfaces.  
**SENSITIVITY TO IMPACT:** Do not puncture  
**METHOD USED:** Estimated  
**FLAMMABLE LIMITS - LEL:** 0.9% **UEL:** 14.0%  
**SENSITIVITY TO STATIC DISCHARGE:** Primarily vapors

### SECTION V - REACTIVITY DATA

**STABILITY:** Stable  
**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizing agents.  
**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Carbon Monoxide, Carbon Dioxide.  
**HAZARDOUS POLYMERIZATION:** Will not occur  
**CONDITIONS TO AVOID:** Open flames, sparks, electrical arcs.

### SECTION VI - HEALTH HAZARD DATA

**INHALATION:** Respiratory tract irritant. May cause dizziness, light-headedness and / or headaches. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.  
**SKIN CONTACT:** Prolonged or repeated contact may cause irritation and dermatitis.  
**EYE CONTACT:** Painful with slight to moderate irritation.  
**INGESTION:** May be harmful or fatal if swallowed.  
**EFFECTS OF CHRONIC OVEREXPOSURE:** Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood.  
**CARCINOGENICITY:** The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.  
**TERATOGENICITY:** Not established **MUTAGENICITY:** Not established  
**MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE:** Not established  
**EMERGENCY AND FIRST AID PROCEDURES:** INHALATION - Remove from exposure, seek medical attention if signs/symptoms persist.  
SKIN - Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.  
EYES - Flush immediately with water for 15 minutes, seek medical attention if irritation persists.  
INGESTION - Do not induce vomiting. Contact physician or poison control center immediately.

### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.  
**WASTE DISPOSAL METHOD:** Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Do not store above 120° F (49° C). Do not store or use near heat, sparks or flame.  
**OTHER PRECAUTIONS:** Avoid contact with eyes and skin. Do not breathe vapors, take internally or smoke while using this product.

### SECTION VIII - CONTROL MEASURES

**RESPIRATORY PROTECTION:** In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator. For concentrations above the TLV (as defined in Section II), use a positive air supplied respirator.  
**VENTILATION:** General ventilation to maintain exposure limits below TLV's as defined in Section II.  
**PROTECTIVE GLOVES:** Chemical resistant gloves such as Neoprene or Nitrile rubber.  
**EYE PROTECTION:** Safety glasses or goggles.  
**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Not established.  
**WORK / HYGIENIC PRACTICES:** Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

### SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.