



**RAINBOW TECHNOLOGY**  
Specialists in Utility Chemicals & Safety Items

261 Cahaba Valley Parkway - Pelham, AL 35124-1146

Tel: 1.800.637.6047 / 205.733.0333

Fax: 1.800.521.6896 / 205.733.8930

[www.rainbowtech.net](http://www.rainbowtech.net)

Woman-Owned Business Enterprise - Founded 1971

# Safety Data Sheet (SDS)

## SECTION I - IDENTIFICATION

**Customer** RAINBOW TECHNOLOGY  
**Product Name** Dry Graphite Lube  
**Product Number** 4688  
**Manufacturer/Supplier** Rainbow Technology Corporation  
 261 Cahaba Valley Parkway  
 Pelham, AL 35124  
 800.637.6047  
[www.rainbowtech.net](http://www.rainbowtech.net)  
**Contact Person** Larry Joe Steeley, Jr.  
**Emergency Information** CHEMTEL 1-800-255-3924  
 813-248-0585 if located outside the U.S.

**Revised Date:** Jun 24, 2022  
**Preparation Date:** Sept 10, 2018

## SECTION II - HAZARDS IDENTIFICATION

**CLASSIFICATION:** Flammable Aerosol: Category 1

**Liquefied Gas**

Skin Irritant: Category 2

Eye Irritant: Category 2A

Specific Target Organ Toxicity (Single Exposure): Category 3

**HAZARD STATEMENT(S): DANGER:** Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. May cause respiratory irritation, drowsiness or dizziness.

This product contains the following percentage of chemicals of unknown toxicity: 0%

**PRECAUTIONARY STATEMENTS:** Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapor and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state, and national regulations.

**SYMBOL:**



**HAZARDS NOT OTHERWISE CLASSIFIED:** N/A

## SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Acetone	67-64-1	30-60%
Isopropyl Alcohol	67-63-0	5-15%
Propane/n-Butane	68476-86-8	15-40%

## SECTION IV - FIRST AID MEASURES

**EYES:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**INGESTION:** Do not induce vomiting unless directed by medical authority. Immediately rinse mouth with water. Drink large quantities (1 qt, 2-4 glasses) of water. Seek immediate medical attention.

**INHALATION:** If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

**SKIN:** Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes immediately. Seek medical attention if irritation develops.

# Safety Data Sheet (SDS)

**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

**CHRONIC HEALTH HAZARDS:** May cause damage to the following organs: kidneys, liver, respiratory, reproductive and central nervous systems.

**NOTE TO PHYSICIAN:** There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

## SECTION V – FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Dry chemical, carbon dioxide, and alcohol foam.

**UNSUITABLE EXTINGUISHING MEDIA:** Water spray/stream.

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Contents under pressure. Exposure to temperatures above 120°F may cause bursting. Flammable.

**HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon

## SECTION VI – ACCIDENTAL RELEASE MEASURES

**PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.

**SPILL:** Clean up with rag or use some non-combustible material like vermiculite, sand or earth.

**WASTE DISPOSAL:** Dispose of in accordance with federal, state, and local regulations. Do not reuse, puncture, or incinerate container. Wrap container and place in trash collection.

**RCRA STATUS:** Waste solvent likely considered U220 (Toluene), hazardous, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

## SECTION VII – HANDLING AND STORAGE

**HANDLING AND STORAGE:** Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use.

**OTHER PRECAUTIONS:** Keep out of the reach of children.

**INCOMPATIBILITY:** Concentrated nitric & sulfuric acid mixtures, oxidizing materials, chloroform, alkalis, chlorine compounds, acids, plastics, rubber, coatings.

## SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	500ppm
Isopropyl Alcohol	400 ppm	200 ppm
Propane/n-Butane	1000 ppm	1000 ppm

**ENGINEERING CONTROLS / VENTILATION:** Normal, forced ventilation required. Local exhaust ventilation is generally preferred.

**RESPIRATORY PROTECTION:** Not required with normal use. Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses and chemical resistant gloves

**ADDITIONAL MEASURES:** Wash hands thoroughly after handling.

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** Black Liquid

**ODOR:** Solvent odor

**ODOR THRESHOLD:** N/D

**pH:** N/A

**MELTING POINT/FREEZING POINT:** N/D

**INITIAL BOILING POINT AND BOILING RANGE:** N/D

# Safety Data Sheet (SDS)

**FLASH POINT:** N/D  
**EVAPORATION RATE:** > 1  
**FLAMMABILITY(solid/gas):** Extremely Flammable Aerosol  
**UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:**  
    **LOWER FLAMMABILITY LIMIT:** N/D  
    **UPPER FLAMMABILITY LIMIT:** N/D  
    **EXPLOSIVE LIMIT LOWER (%):** N/D  
    **EXPLOSIVE LIMIT UPPER (%):** N/D  
**VAPOR PRESSURE (mm Hg):** 77.3 @ 77°F (25°C)  
**VAPOR DENSITY (AIR=1):** 4.5  
**RELATIVE DENSITY (H<sub>2</sub>O=1):** 0.830 @ 77° F (25°C)  
**SOLUBILITY(IES):** Miscible  
**PARTITION COEFFICIENT: n-OCTANOL/WATER (K<sub>ow</sub>):** N/D  
**AUTOIGNITION TEMPERATURE:** N/D  
**DECOMPOSITION TEMPERATURE:** N/D  
**VISCOSITY:** N/D

## SECTION X – STABILITY AND REACTIVITY

**REACTIVITY:** None Known  
**CHEMICAL STABILITY:** Stable  
**POSSIBLE HAZARDOUS REACTIONS:** None Known  
**CONDITIONS TO AVOID:** None known  
**INCOMPATIBLE MATERIALS:** Concentrated nitric & sulfuric acid mixtures, oxidizing materials, chloroform, alkalis, chlorine compounds, acids, plastics, rubber, coatings.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Oxides of carbon

## SECTION XI – TOXICOLOGICAL INFORMATION

**TOXICOLOGICAL INFORMATION:** Acetone (67-64-1) LD<sub>50</sub> (Oral, Rabbit) 5340 mg/kg; LD<sub>50</sub> (Dermal, Rabbit) 20000 mg/kg  
**ROUTES OF ENTRY:** Ingestion, Inhalation, Skin  
**EYES:** Redness, irritation, causes temporary corneal opacity  
**INGESTION:** May cause nausea, diarrhea, vomiting, depending on the amount ingested.  
**INHALATION:** Causes dizziness, anesthesia, possibly death if breathed directly.  
**SKIN:** Causes severe irritation, localized defatting.  
**MEDICAL CONDITION AGGRAVATED:** Pre-existing conditions of the skin, liver, kidneys, CNS and respiratory system.  
**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision  
Skin: defatting and dermatitis  
**CHRONIC HEALTH HAZARDS:** May cause damage to the following organs: kidneys, liver, respiratory, reproductive and central nervous systems.  
**CARCINOGENICITY:** OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

## SECTION XII – ECOLOGICAL INFORMATION

**ECOTOXICITY:** Acetone (67-64-1) LC<sub>50</sub> (Trout, 96hr) 5540 mg/L; LC<sub>50</sub> (Bluegill, 96hr) 8300 mg/L; LC<sub>50</sub> (Fathead Minnow, 96hr) 7500 mg/L Isopropyl Alcohol (67-63-0) LC<sub>50</sub> (Fathead Minnow, 96 hrs) 9640 mg/L  
**PERSISTENCE AND DEGRADABILITY:** This product is biodegradable.  
**BIOACCUMULATIVE POTENTIAL:** This product is not expected to bioaccumulate.  
**MOBILITY IN SOIL:** This product is mobile in soil.  
**OTHER ADVERSE EFFECTS:** This material is toxic to aquatic life.

## SECTION XIII – DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:** Dispose of in accordance with federal, state, and local regulations. Do not reuse, puncture, or incinerate container. Wrap container and place in trash collection.  
**RCRA STATUS:** Waste solvent likely considered U220 (Toluene), hazardous, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

# Safety Data Sheet (SDS)

## SECTION XIV - TRANSPORT INFORMATION

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.  
**HAZARD CLASS/DIVISION:** 2.1  
**UN/NA NUMBER:** UN 1950  
**PACKING GROUP:** N/A

### AIR SHIPMENT

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.  
**HAZARD CLASS/DIVISION:** 2.1  
**UN/NA NUMBER:** UN 1950  
**PACKING GROUP:** N/A

### SHIPPING BY WATER:

**VESSEL (IMO/IMDG)**  
**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.  
**HAZARD CLASS/DIVISION:** 2.1  
**UN/NA NUMBER:** UN 1950  
**PACKING GROUP:** N/A  
**ENVIRONMENTAL HAZARDS WATER:** N/A

## SECTION XV - REGULATORY INFORMATION

**TSCA STATUS:** All Chemicals are listed or exempt.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** Acetone (67-64-1) Reportable Quantity = 5,000 lbs

**SARA 311/312 HAZARD CATEGORIES:** Acute Health, Fire, Pressure.

**SARA 313 REPORTABLE INGREDIENTS:** None

**CLEAN WATER ACT:** None

**STATE REGULATIONS:** Acetone (67-64-1) Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, Illinois chemical safety act, New York release reporting list, **RTK** - RI, PA, FL, MN, MA, NJ; Massachusetts spill list, New Jersey spill list, Louisiana spill reporting, California List of Hazardous Substances (8 CCR 339): Acetone TSCA 8(b) inventory: Acetone TSCA 4(a) final test rules: Acetone TSCA 8(a) IUR: Acetone

**INTERNATIONAL REGULATIONS:** Acetone (67-64-1) Australia, China, Europe (EINECS), Japan, Korea, United Kingdom, Canada, WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects (TOXIC). p. 6; DSCL (EEC): R11- Highly flammable. R36- Irritating to eyes. S9- Keep container in a well-ventilated place. S16- Keep away from ignition sources. S26- In case of eye contact, rinse immediately with plenty of water and seek medical advice.

**VOLATILE ORGANIC COMPOUNDS (VOC):** 43%

**NFPA HEALTH:** 2

**HMIS HEALTH:** 2

**NFPA FLAMMABILITY:** 3

**HMIS FLAMMABILITY:** 3

**NFPA REACTIVITY:** 0

**HMIS REACTIVITY:** 0

**NFPA OTHER:** None

**HMIS PROTECTION:** B

## SECTION XVI - OTHER INFORMATION

N/A = Not Applicable; N/D = Not Determined

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the

# Safety Data Sheet (SDS)

manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.