



RAINBOW TECHNOLOGY
Specialists in Utility Chemicals & Safety Items

261 Cahaba Valley Parkway - Pelham, AL 35124-1146

Tel: 1.800.637.6047 / 205.733.0333

Fax: 1.800.521.6896 / 205.733.8930

www.rainbowtech.net

Woman-Owned Business Enterprise - Founded 1971

Safety Data Sheet (SDS)

1 Identification

Product Name: Vandalism & Graffiti Remover
Product Number: 79314
Date of Issue: 27-April-2017
Revision Date: 5-July-2018
Supplier's Details: Rainbow Technology Corporation
 261 Cahaba Valley Parkway
 Pelham, AL 35124-1146
Contact Person: Larry Joe Steeley, Jr.
Emergency Contact (24 hrs.): Chem-Tel (800) 255-3924

2 Hazard(s) identification

· Classification of the substance or mixture



GHS 04 gas cylinder

H280 Contains gas under pressure; may explode if heated.



GHS02 Flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child. Route of exposure: Inhalative.

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalative.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

toluene
acetone
butanone

· **Hazard statements**

H280 Contains gas under pressure; may explode if heated.
H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child. Route of exposure: Inhalative.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the central nervous system through prolonged or repeated exposure.
Route of exposure: Inhalative.
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe mist/vapours/spray.
P281 Use personal protective equipment as required.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P302+P352 If on skin: Wash with plenty of water.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:** Pressurized container: May burst if heated.

· **Hazard description:**

· **WHMIS-symbols:**

A - Compressed gas
B5 - Flammable aerosol
D2A - Very toxic material causing other toxic effects



· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 4
Reactivity = 3

Safety Data Sheet (SDS)

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = *1
FIRE	4	Fire = 4
REACTIVITY	3	Reactivity = 3

* - Indicates a long term health hazard from repeated or prolonged exposures.

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

67-64-1	acetone Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	50-100%
108-88-3	toluene Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
72-28-5	Isobutane Flam. Gas 1, H220	10-25%
111-76-2	2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 Flam. Liq. 4, H227	2.5-10%
78-93-3	butanone Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	≤ 2.5%
74-98-6	propane Flam. Gas 1, H220 Press. Gas, H280	≤ 2.5%

· **Dangerous Components (Alternative Classifications):**

67-64-1	acetone Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	50-100%
108-88-3	toluene Flam. Liq. 2, H225 Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	25-50%

(Contd. on page 4)

Safety Data Sheet (SDS)

		(Contd. of page 3)
72-28-5	Isobutane ⚠ Flam. Gas 1, H220	10-25%
111-76-2	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 Flam. Liq. 4, H227	2.5-10%
78-93-3	butanone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336	≤ 2.5%

4 First-aid measures

- **Description of first aid measures**

- **General information:** Take affected persons out into the fresh air.

- **After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

- **Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Nausea

Gastric or intestinal disorders when ingested.

Breathing difficulty

Allergic reactions

Coughing

Irritant to skin and mucous membranes.

Irritant to eyes.

Disorientation

- **Danger**

Danger of impaired breathing.

Vapours may cause drowsiness and dizziness.

May damage fertility or the unborn child. Route of exposure: Inhalative. Route of exposure: Inhalative.

Danger of disturbed cardiac rhythm.

Danger of pulmonary edema.

Condition may deteriorate with alcohol consumption.

Repeated exposure may cause skin dryness or cracking.

(Contd. on page 5)

(Contd. of page 4)

Danger of serious damage to health by prolonged exposure.

· **Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

In cases of irritation to the lungs, initial treatment with Dexamethason metered aerosol.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

If swallowed or in case of vomiting, danger of entering the lungs.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Water spray

Water fog / haze

Foam

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

· **For safety reasons unsuitable extinguishing agents:** Water stream.

· **Special hazards arising from the substance or mixture**

Danger of receptacles bursting because of high vapor pressure if heated.

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information**

Eliminate all ignition sources if safe to do so.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

If aerosols are bursting, stay clear until safe. Aerosol containers can be projectiles when bursting.

Cool endangered product with water spray.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

If containers are leaking, use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation.

Keep away from ignition sources.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Allow to evaporate.

Absorb liquid components with liquid-binding material.

Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Send for recovery or disposal in suitable receptacles.

(Contd. on page 6)

· **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· **Precautions for safe handling**

Keep away from heat and direct sunlight.
Use only in well ventilated areas.
Pressurized container: Do not pierce or burn, even after use.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.
Fumes can combine with air to form an explosive mixture.
Flammable gas-air mixtures may be formed in empty receptacles.
Do not spray on a naked flame or any incandescent material.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurized containers.
Provide ventilation for receptacles.
Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.
Store away from oxidizing agents.

· **Further information about storage conditions:**

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
Protect from frost.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm BEI
EL (Canada)	Short-term value: 500 ppm Long-term value: 250 ppm

Safety Data Sheet (SDS)

(Contd. of page 6)

EV (Canada) Short-term value: 750 ppm
Long-term value: 500 ppm

LMPE (Mexico) Short-term value: 750 ppm
Long-term value: 500 ppm
A4, IBE

108-88-3 toluene

PEL (USA) Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV (USA) Long-term value: 75 mg/m³, 20 ppm
BEI

EL (Canada) Long-term value: 20 ppm
R

EV (Canada) Long-term value: 20 ppm

LMPE (Mexico) Long-term value: 20 ppm
A4, IBE

111-76-2 2-butoxyethanol

PEL (USA) Long-term value: 240 mg/m³, 50 ppm
Skin

REL (USA) Long-term value: 24 mg/m³, 5 ppm
Skin

TLV (USA) Long-term value: 97 mg/m³, 20 ppm
BEI

EL (Canada) Long-term value: 20 ppm

EV (Canada) Long-term value: 20 ppm
Skin

LMPE (Mexico) Long-term value: 20 ppm
A3, IBE

78-93-3 butanone

PEL (USA) Long-term value: 590 mg/m³, 200 ppm

REL (USA) Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm

TLV (USA) Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
BEI

EL (Canada) Short-term value: 100 ppm
Long-term value: 50 ppm

EV (Canada) Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm

LMPE (Mexico) Short-term value: 300 ppm
Long-term value: 200 ppm
IBE

(Contd. on page 8)

Safety Data Sheet (SDS)

(Contd. of page 7)

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm
 REL (USA) Long-term value: 1800 mg/m³, 1000 ppm
 TLV (USA) refer to Appendix F
 EL (Canada) Long-term value: 1000 ppm
 EV (Canada) Long-term value: 1.000 ppm
 LMPE (Mexico) Long-term value: 1000 ppm

· Ingredients with biological limit values:

67-64-1 acetone

BEI (USA) 50 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

108-88-3 toluene

BEI (USA) 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

111-76-2 2-butoxyethanol

BEI (USA) 200 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: Butoxyacetic acid with hydrolysis

78-93-3 butanone

BEI (USA) 2 mg/L
 Medium: urine
 Time: end of shift
 Parameter: MEK

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.
 Keep away from foodstuffs, beverages and feed.
 Wash hands before breaks and at the end of work.

(Contd. on page 9)

Do not inhale gases / fumes / aerosols.
Pregnant women should strictly avoid inhalation or skin contact.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

Suitable respiratory protective device recommended.
For spills, respiratory protection may be advisable.
Use suitable respiratory protective device in case of insufficient ventilation.
NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

No further relevant information available.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Colorless
· Odor:	Acetone-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	104 °C (219 °F)

· **Flash point:** < 2 °C (< 36 °F) (liquid)

(Contd. of page 9)

- **Flammability (solid, gaseous):** Not applicable.
- **Auto-ignition temperature:** Not determined.
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- **Explosion limits:**
 - Lower:** Not determined.
 - Upper:** Not determined.
- **Vapor pressure at 21 °C (70 °F):** 20 - 35 psig
- **Density at 21 °C (70 °F):** 0.822 g/cm³ (6.86 lbs/gal)
- **Relative density** Not determined.
- **Vapour density** > 1 (Air=1)
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
- **VOC content:** 49.97 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications.
Danger of receptacles bursting because of high vapor pressure if heated.
- **Possibility of hazardous reactions**

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Extremely flammable aerosol.
Used empty containers may contain product gases which form explosive mixtures with air.
Toxic fumes may be released if heated above the decomposition point.
Reacts violently with oxidizing agents.
- **Conditions to avoid**

Keep away from heat and direct sunlight.
Excessive heat and contact with oxidizers.
Keep ignition sources away - Do not smoke.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 11)

(Contd. of page 10)

- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Hydrocarbons

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
Inhalation of concentrated vapors as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.
Toxic and/or corrosive effects may be delayed up to 24 hours.
Suspected of damaging fertility or the unborn child. Route of exposure: Inhalative. Route of exposure: Inhalative.

- **Carcinogenic categories**

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Repeated Dose Toxicity:** May cause damage to organs through prolonged or repeated exposure.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 12)

Safety Data Sheet (SDS)



(Contd. of page 11)

- **Additional ecological information:**
- **General notes:**
 - Avoid transfer into the environment.
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
 - Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - Contact waste processors for recycling information.
 - Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
 - The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Waste disposal key:** EPA RCRA Code (USA) : D001, D035 .
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
-  Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 1 L (0.3 gal).
- **DOT** Aerosols, flammable
- **ADR** 1950 AEROSOLS, flammable
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 2.1

(Contd. on page 13)

Safety Data Sheet (SDS)

(Contd. of page 12)

· **Label** 2.1

· **ADR**




· **Class** 2 5F Gases
 · **Label** 2.1

· **IMDG**



· **Class** 2 Gases
 · **Label** 2.1

· **IATA**



· **Class** 2.1
 · **Label** 2.1
 · **Packing group**
 · **DOT, ADR, IMDG, IATA** Not Regulated
 · **Environmental hazards:**
 · **Marine pollutant:** No
 · **Special precautions for user** Warning: Gases
 · **Danger code (Kemler):** -
 · **EMS Number:** F-D,S-U
 · **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
 · **Transport/Additional information:**
 · **DOT**
 · **Quantity limitations** On passenger aircraft/rail: 75kg
 On cargo aircraft only: 150kg

· **ADR**
 · **Excepted quantities (EQ)** Code: E0
 Not permitted as Excepted Quantity

· **IMDG**
 · **Limited quantities (LQ)** 1000mL
 · **Excepted quantities (EQ)** Code: E0
 Not permitted as Excepted Quantity
 · **UN "Model Regulation":** UN1950, Aerosols, 2.1

(Contd. on page 14)

Safety Data Sheet (SDS)

(Contd. of page 13)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- SARA

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
111-76-2	2-butoxyethanol
78-93-3	butanone

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3	toluene
----------	---------

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
108-88-3	toluene	II
111-76-2	2-butoxyethanol	NL
78-93-3	butanone	I

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
111-76-2	2-butoxyethanol	3

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
108-88-3	toluene	A4
111-76-2	2-butoxyethanol	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **State Right to Know Listings**

None of the ingredients is listed.

(Contd. on page 15)

(Contd. of page 14)

· **Canadian substance listings:**

· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
· Canadian Ingredient Disclosure list (limit 1%)	
67-64-1	acetone
108-88-3	toluene
111-76-2	2-butoxyethanol
78-93-3	butanone

· **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- WHMIS: Workplace Hazardous Materials Information System (Canada)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Gas 1: Flammable gases, Hazard Category 1
- Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas: Gases under pressure: Compressed gas
- Flam. Liq. 2: Flammable liquids, Hazard Category 2
- Flam. Liq. 4: Flammable liquids, Hazard Category 4
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
- Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
- Repr. 2: Reproductive toxicity, Hazard Category 2
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1