

Distributed by **Rainbow Technology Corp.**Tel: 1.800.637.6047 / 205.733.0333
RTC Products #79374

Page 1/9

## Safety Data Sheet acc. to OSHA HCS

Printing Date 06/22/2016 Revision Number 1 Revision Date 06/22/2016

### 1 Identification

- · Product identifier
- · Trade name: Q-Tel 2004 C-Cement
- · Relevant identified uses of the substance or mixture. Adhesive
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Royal Adhesives & Sealants Canada Ltd

266 Humberline Drive - Toronto, Ontario, Canada M9W 5X1

Tel. +1 416-679-5676 Fax: +1 416-679-0511

- · Information department: Environment protection department.
- · Emergency telephone number:

Emergency Telephone Number: CANUTEC Collect: (613) 996-6666 (24-hour hotline)

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

(Contd. on page 2)

Printing Date 06/22/2016 Revision Number 1 Revision Date 06/22/2016

Trade name: Q-Tel 2004 C-Cement

(Contd. of page 1)

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Do NOT induce vomiting.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



1 Health = 1

3 Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture
- · Hazardous components:

142-82-5 heptane

50-100%

Printing Date 06/22/2016 Revision Number 1 Revision Date 06/22/2016

Trade name: Q-Tel 2004 C-Cement

(Contd. of page 2)

### 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air or oxygen; call for doctor.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, sand, extinguishing powder. Do not use water.

Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.

(Contd. on page 4)

Printing Date 06/22/2016 Revision Number 1 Revision Date 06/22/2016

Trade name: Q-Tel 2004 C-Cement

(Contd. of page 3)

- · Information about storage in one common storage facility: Store away from oxidizing agents.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

#### 1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m³ REL Long-term value: 3.5 mg/m³ TLV Long-term value: 3. mg/m³

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

PVC gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses with side shields.



Tightly sealed goggles

(Contd. on page 5)

Printing Date 06/22/2016 Revision Number 1 Revision Date 06/22/2016

Trade name: Q-Tel 2004 C-Cement

· Body protection: Protective work clothing

(Contd. of page 4)

	y . y
Information on basic physical and c	chemical properties
General Information Appearance:	
Form:	Liquid
Color:	Black
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point:	Undetermined.
Boiling point:	98 °C (208 °F)
Flash point:	-4 °C (25 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	215 °C (419 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Flammable limits:	
Lower:	1.1 Vol %
Upper:	6.7 Vol %
Vapor pressure at 20 °C (68 °F):	48 hPa (36 mm Hg)
Specific gravity at 20 °C (68 °F):	$0.84 \ g/cm^3 \ (7.01 \ lbs/gal)$
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Solids content:	not available
Other information	No further relevant information available.

## 10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 6)

Printing Date 06/22/2016 Revision Number 1 Revision Date 06/22/2016

Trade name: Q-Tel 2004 C-Cement

(Contd. of page 5)

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, flames, sparks.
- · Incompatible materials:

Reacts with oxidizing agents.

Reacts with acids.

Reacts with alkali (lyes).

· Hazardous decomposition products:

Carbon monoxide

Carbon dioxide

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: May irritate the eye.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1333-86-4 Carbon black

2*B* 

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

-USA

Printing Date 06/22/2016 Revision Number 1 Revision Date 06/22/2016

Trade name: Q-Tel 2004 C-Cement

(Contd. of page 6)

### 13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must be specially treated adhering to official regulations.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number	
· DOT, ADR, IMDO	G, IATA
. IIN proper shipping	na namo

UN1133

· UN proper shipping name · DOT

Adhesives

• ADR 1133 Adhesives solution, ENVIRONMENTALLY HAZARDOUS • IMDG ADHESIVES solution, MARINE POLLUTANT

· IATA ADHESIVES solution

- · Transport hazard class(es)
- $\cdot DOT$



ClassLabel3 Flammable liquids3

· ADR, IMDG





· Class· Label3 Flammable liquids3

 $\cdot$  IATA



· Class 3 Flammable liquids

· Label

· Packing group · DOT, ADR, IMDG, IATA

• Environmental hazards: Product contains environmentally hazardous substances: heptane

· Marine pollutant: Yes

Symbol (fish and tree)
• Special marking (ADR):

Symbol (fish and tree)

· Special precautions for user Warning: Flammable liquids

· Danger code (Kemler):

(Contd. on page 8)

Printing Date 06/22/2016 Revision Number 1 Revision Date 06/22/2016

Trade name: Q-Tel 2004 C-Cement

Contd. of page 7)

• EMS Number: F-E,S-D

• Segregation groups Liquid halogenated hydrocarbons

• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

• UN "Model Regulation": UN1133, Adhesives solution, ENVIRONMENTALLY HAZARDOUS, 3, II

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

142-82-5 heptane

D

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · National regulations:
- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### <u> 16 Other information</u>

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from (Contd. on page 9)

Printing Date 06/22/2016 Revision Number 1 Revision Date 06/22/2016

Trade name: Q-Tel 2004 C-Cement

(Contd. of page 8)

the use or reliance on the information set forth in the SDS.

- · Department issuing SDS: Environment protection department.
- · Creation Date: 03/31/2015
- · Date of preparation / last revision 06/22/2016 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

- USA