

Distributed by
Rainbow Technology Corp.
Tel: 1.800.637.6047 / 205.733.0333
RTC Product #87030

Distributed by: Rainbow Technology Corp.
800.637.6047 or 205.733.0333
RTC Product # 87030

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: 809
IDENTITY: NO CHLOR BRAKE CLEAN
Revision Date: 02/11/2009

Section I

Manufacturer's Name: QUEST CHEMICAL CORPORATION
Address: 12255 FM 529
NORTHWOODS INDUSTRIAL PARK
HOUSTON
State: TX Zip Code: 77041
Telephone Numbers:
Emergency: 800/255-3924
Information: 713/8968188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 4 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
ACETONE	67-64-1	1000 PPM	750 PPM	N/A	---
CARBON DIOXIDE	124-38-9	5000 PPM	5000 PPM	N/A	---
HEPTANE	142-82-5	400 PPM	400 PPM	N/A	---
PETROLEUM NAPHTHA VM & P *	64742-89-8	500 PPM	300 PPM	N/A	---
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----
-----	-----	-----	-----	-----	-----

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 140 F Specific Gravity (water=1) 0.75
Vapor Pressure(mm Hg) 180 Melting Point: -130 F
Vapor Density(AIR=1) 2.62 Evaporation Rate: 8.7
Solubility in Water: 87% (Butyl Acetate=1)
Appearance and Odor: CLEAR WATER WHITE SPRAY, ALIPHATIC SOLVENT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used): <10F TCC Flammable Limits: LEL:1.2 UEL: 7.5
Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: FLAMMABLE CONTENTS UNDER PRESSURE.
TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING. MAY DEVELOP A FLAMMABLE
ATMOSPHERE IN CONFINED AREAS.

Safety Data Sheet (SDS)

Section 10: REACTIVITY DATA

PRODUCT NUMBER: 815

Stability: Stable. Conditions to Avoid: TEMPERATURES ABOVE 120 F
 (40 C) /
 Incompatibility (Materials to Avoid): NONE KNOWN

Exothermic Decomposition or Polymerization: NONE KNOWN

Exothermic Degradation: May Occur Will Not Occur: X
 Conditions to Avoid: NONE KNOWN

Section 11: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
 Health Hazard/Label and Phrases:
 IRRITATION: SKIN/ EYES, IRRITATION: MILD, RPH; R410 (ACUTE TOXIC) MAY
 CAUSE DYSRHYTHMIA DEPRESSION OF PLACENTA. EYES: IRRITATION, H302 (ACUTE TOXIC)

Cardiotoxicity: R410 (ACUTE TOXIC) IARC Monographs: NO GHS07 (CORROSIVE)
 Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Residue: Control and Control by Exposure: NONE

Emergency and First Aid Procedures: INHALATION: MOVE TO FRESH AIR. APPLY
 ARTIFICIAL RESPIRATION IF INDICATED. INGESTION: DO NOT INDUCE VOMITING
 FOR ACUTE TOXICITY IMMEDIATELY. SKIN: WASH WITH SOAP AND WATER. EYES:
 FLUSH WITH WATER AND CONTACT PHYSICIAN.

Section 12: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken if case material is released or spilled: Wipe up with
 1/2 cup of 50:50 LIME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: INSTEAD OF REPORTING TO AUTHORITIES WITH FEDERAL,
 STATE AND LOCAL REGULATIONS.

Precautions to be taken in handling and storage: DO NOT USE OR STORE NEAR
 HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120F MAY CAUSE R410 (ACUTE TOXIC).

Other Precautions: VAPOR MAY ACCUMULATE IN LOW LYING AREAS.

Section 13: CONTROL MEASURES

Respiratory protection: USE ONLY IN WELL VENTILATED AREAS.

Ventilation: Local Exhaust Adequate

Method: A: N/A

Special: N/A

Other: N/A

Personal Protective Equipment:

Eye Protection: SAFETY GOGGLES AND BLOWSCREENS RECOMMENDED (SEE MSDS AND LABEL).

Other Protective Clothing or Equipment:

N/A

Wash Frequency/Procedure:

WASH HANDS AFTER USE.